



### Key features

- Meet UL, CE certification requirements
- Low ripple and noise
- Over load protection ,short circuit protection
- High efficiency, high density, fine quality and low price
- Industrial/military design
- Six sides metal shielding, international standard pin
- 100% test and work
- 3 Years product warranty



### Electrical specifications

Model	Input voltage	Output Power(W)	Output voltage(V)	Output current(A)	Ripple(mv)	Efficiency (%)
DPM10-12S03	12(9-18)	9.9	3.3	3	100	78%
DPM10-12S05		10	5.0	2	100	80%
DPM10-12S12		10.8	12.0	0.9	100	83%
DPM10-12S15		10.5	15.0	0.7	100	85%
DPM10-12S24		10.8	24.0	0.45	50	86%
DPM10-12D12		10	±12	0.42	50	83%
DPM10-12D15		10	±15	0.33	50	84%
DPM10-18S03	18(9-36)	9.9	3.3	3	100	78%
DPM10-18S05		10	5.0	2	100	80%
DPM10-18S12		10.8	12.0	0.9	100	83%
DPM10-18S15		10.5	15.0	0.7	100	85%
DPM10-18S24		10.8	24.0	0.45	50	86%
DPM10-24S03	24(18-36)	9.9	3.3	3	50	78%
DPM10-24S05		10	5.0	2	50	80%
DPM10-24S12		10.8	12.0	0.9	50	83%
DPM10-24S15		10.5	15.0	0.7	50	85%
DPM10-24S24		10.8	24.0	0.45	50	86%
DPM10-24D12		10	±12	0.42	50	83%
DPM10-24D15		10	±15	0.33	50	84%
DPM10-48S03	48(36-72)	9.9	3.3	3	50	78%
DPM10-48S05		10	5.0	2	50	80%



DPM10-48S12		10.8	12.0	0.9	50	83%
DPM10-48S15		10.5	15.0	0.7	50	85%
DPM10-48S24		10.8	24.0	0.45	50	86%
DPM10-48D12		10	±12	0.42	50	83%
DPM10-48D15		10	±15	0.33	50	84%
DPM10-110S03	110(70-140)	9.9	3.3	3	50	78%
DPM10-110S05		10	5.0	2	50	80%
DPM10-110S12		10.8	12.0	0.9	50	83%
DPM10-110S15		10.5	15.0	0.7	50	85%
DPM10-110S24		10.8	24.0	0.45	50	86%
DPM10-110D12		10	±12	0.42	50	83%
DPM10-110D15		10	±15	0.33	50	84%
DPM15-18S03	18(9-36)	9.9	3.3	3	100	78%
DPM15-18S05		15	5.0	3	100	80%
DPM15-18S12		15	12.0	1.25	100	83%
DPM15-18S15		15	15.0	1	100	84%
DPM15-18S24		15	24.0	0.625	100	84%
DPM15-24D12	24(18-36)	15	±12	0.625	100	83%
DPM15-24D15		15	±15	0.5	100	84%
DPM15-24S03		9.9	3.3	3	100	78%
DPM15-24S05		15	5.0	3	100	80%
DPM15-24S12		15	12.0	1.25	100	83%
DPM15-24S15		15	15.0	1	100	84%
DPM15-24S24		15	24.0	0.625	100	84%
DPM15-24D12		15	±12	0.625	100	83%
DPM15-24D15	15	±15	0.5	100	84%	
DPM15-48S03	48(36-72)	9.9	3.3	3	100	78%
DPM15-48S05		15	5.0	3	100	80%
DPM15-48S12		15	12.0	1.25	100	83%
DPM15-48S15		15	15.0	1	100	85%
DPM15-48S24		15	24.0	0.625	100	86%
DPM15-48D12		15	±12	0.625	100	83%
DPM15-48D15		15	±15	0.5	100	84%
DPM15-110S03	110(70-140)	9.9	3.3	3	100	78%
DPM15-110S05		15	5.0	3	100	80%
DPM15-110S12		15	12.0	1.25	100	83%
DPM15-110S15		15	15.0	1	100	85%
DPM15-110S24		15	24.0	0.625	100	86%
DPM15-110D12		15	±12	0.625	100	83%
DPM15-110D15		15	±15	0.5	100	84%