



six sides metal terminal of DC/DC module
power supply



Key features

- Meet UL, CE certification requirements
- Low ripple and noise
- Internal filter
- Over load protection ,short circuit protection
- High efficiency, high density, fine quality and low price
- Industrial/military design
- Six sides metal shielding,lead terminal connect,chassis type mounted
- 100% test and work
- 3 Years product warranty
- Soft start and remote on / off control

DMP60 series --- a wiring module power supply offered by Zhongyiguang. The output power of this series module power supply is 60W, small size (98*52*22mm) and isolation voltage up to 1kv, etc. The product is safe and reliable, which has a good EMC. EMC and Safety specifications meet many related standards ,such as IEC/EN61000-4, CISPR22/EN55022, UL60950/EN60950/EN60601. This series of products are widely used in industrial, office and civil industries. If applied to a relatively harsh environment electromagnetic compatibility, it must be referenced the application circuit.

Electrical specifications

Model	Input voltage(V)	Output voltage(V)	Output current(A)	Output power(W)	MAX capacitive load(uF)	Ripple and noise(mV)	Efficiency %
DPM30-12S03-EB	12 (9-18)	3.3	6	19.8	3300	100	80%
DPM30-12S05-EB		5.0	6	30	3300	100	84
DPM30-12S12-EB		12.0	2.5	30	560	100	85
DPM30-12S15-EB		15.0	2	30	470	100	85
DPM30-12S24-EB		24.0	1.25	30	100	100	86
DPM30-24S03-EB	24 (18-36)	3.3	6	19.8	3300	100	80
DPM30-24S05-EB		5.0	6	30	3300	100	84
DPM30-24S12-EB		12.0	2.5	30	560	100	85



DPM30-24S15-EB		15.0	2	30	470	100	85
DPM30-24S24-EB		24.0	1.25	30	100	100	86
DPM30-48S03-EB	48 (36-72)	3.3	6	19.8	3300	100	80
DPM30-48S05-EB		5.0	6	30	3300	100	84
DPM30-48S12-EB		12.0	2.5	30	560	100	85
DPM30-48S15-EB		15.0	2	30	470	100	85
DPM30-48S24-EB		24.0	1.25	30	100	100	86
DPM30-110S03-EB		110 (70-140)	3.3	6	19.8	3300	100
DPM30-110S05-EB	5.0		6	30	3300	100	84
DPM30-110S12-EB	12.0		2.5	30	560	100	85
DPM30-110S15-EB	15.0		2	30	470	100	85
DPM30-110S24-EB	24.0		1.25	30	100	100	86
DPM30-300S12-EB	300 (200-400)	12.0	2.5	30	560	100	85
DPM30-300S15-EB		15.0	2	30	470	100	85
DPM30-300S24-EB		24.0	1.25	30	100	100	86
DPM60-12S03-EB	12 (9-18)	3.3	8	26.4	3300	100	80
DPM60-12S05-EB		5.0	8	40	3300	100	84
DPM60-12S12-EB		12.0	5	60	560	100	85
DPM60-12S15-EB		15.0	4	60	470	100	85
DPM60-12S24-EB		24.0	2.5	60	100	100	86
DPM60-24S03-EB	24 (18-36)	3.3	8	26.4	3300	100	80
DPM60-24S05-EB		5.0	8	40	3300	100	84
DPM60-24S12-EB		12.0	5	60	560	100	85
DPM60-24S15-EB		15.0	4	60	470	100	85